

Product datasheet

Specifications



Spacial S3D plain door with mount.plate. H300xW300xD200 IP66 IK10 RAL7035.

Local distributor code: 392865966 NSYS3D3320P

EAN Code : 3606480159718

Main

Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	300 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	200 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 mm double-bar lock
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element
Material	Enclosure: steel Mounting plate: galvanised steel
Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	DNV cUL GL BV

LR
UL

Net weight 5.47 kg

Environment

NEMA degree of protection NEMA 4X/13

IK degree of protection IK10 conforming to IEC 62262

IP degree of protection IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 25.0 cm

Package 1 Width 31.0 cm

Package 1 Length 32.0 cm

Package 1 Weight 5.47 kg

Unit Type of Package 2 PAM

Number of Units in Package 2 84

Package 2 Height 207.0 cm

Package 2 Width 100.0 cm

Package 2 Length 120.0 cm

Package 2 Weight 477.0 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

RoHS exemption information [Yes](#)

Environmental Disclosure [Product Environmental Profile](#)

Contractual warranty

Warranty 18 months

Recommended replacement(s)